SAFETY DATA SHEET



1. Identification

Product identifier Hexanes

Other means of identification

CAS number 110-54-3
Synonyms n-Hexane

Recommended useGeneral purpose solvent.

Recommended restrictions Use in accordance with supplier's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company NameGreenfield Global USA Inc.Address1101 Isaac Shelby Drive

Shelbyville, KY 40065

USA

 Telephone
 502.232.7600

 Fax
 502.633.6100

Company Name Greenfield Global USA Inc.

Address 58 Vale Road

Brookfield, CT 06804

USA

 Telephone
 203.740.3471

 Fax
 203.740.3481

Emergency phone number

USA CHEMTREC: 1.800.424.9300 (CCN 17213)
International CHEMTREC: +1.703.527.3887 (CCN 17213)

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSkin corrosion/irritationCategory 2Reproductive toxicityCategory 2

Specific target organ toxicity, single exposure Category 3 narcotic effects
Specific target organ toxicity, repeated Category 2 (nervous system)

exposure (inhalation)

Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, Category 2

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes skin irritation. Suspected of damaging fertility or the

unborn child. May cause drowsiness or dizziness. May cause damage to organs (nervous system) through prolonged or repeated exposure by inhalation. May be fatal if swallowed and enters

airways. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair):

Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish. Collect

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up. **Storage**

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information None.

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS number	%
Hexanes	n-Hexane	110-54-3	100

Composition comments

All concentrations are in percent by weight unless otherwise indicated.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation

occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do.

Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, Ingestion

keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and

delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water

Indication of immediate

immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation.

medical attention and special treatment needed

Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed. Combustion products may include: carbon oxides.

SDS US Hexanes 2/9 Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods General fire hazards Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool.

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is insoluble in water and will spread on water surfaces. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all

environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not breathe mist/vapors. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

SDS US Hexanes 3/9 Version #: 01 Revision date: -Issue date: 22-January-2019

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Material	Туре	, Value	Value	
Hexanes (CAS 110-54-3)	PEL	1800 mg/m3		
		500 ppm		
US. ACGIH Threshold Limit Value	es			
Material	Туре	Value		
Hexanes (CAS 110-54-3)	TWA	50 ppm		
US. NIOSH: Pocket Guide to Che	mical Hazards			
Material	Туре	Value		
Hexanes (CAS 110-54-3)	TWA	180 mg/m3		

Biological limit values

ACGIH Biological Exposure Indices

Material	Value	Determinant	Specimen	Sampling Time
Hexanes (CAS 110-54-3)	0.5 mg/l	2,5-Hexanedio ne, without hydrolysis	Urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Hexanes (CAS 110-54-3)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Hexanes (CAS 110-54-3)

Can be absorbed through the skin.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

50 ppm

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical goggles are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Gloves of nitrile rubber, PVA or Viton are

recommended. Suitable gloves can be recommended by the glove supplier. Be aware that the

liquid may penetrate the gloves. Frequent change is advisable.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Respirator type: Chemical respirator with

organic vapor cartridge.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Colorless.

Hexanes SDS US

945636 Version #: 01 Revision date: - Issue date: 22-January-2019

Odor Not available.
Odor threshold Not available.
pH Not available.
Melting point/freezing point -139 °F (-95 °C)

Initial boiling point and boiling

range

156.2 °F (69 °C)

Flash point -7.6 °F (-22.0 °C) closed cup

Evaporation rate Not available.
Flammability (solid, gas) Not applicable.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

1.2 % v/v

Flammability limit - upper

(%)

7.7 % v/v

Vapor pressure 176 hPa (132.0 mmHg)

Vapor density 3

Relative density 0.659 (77 °F (25 °C))

Solubility(ies)

Solubility (water) Not soluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 437 °F (225 °C)

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 0.65 g/cm3 at 25 °C

Dynamic viscosity 0.29 mPa.s (77 °F (25 °C))

Explosive properties Not explosive.

Kinematic viscosity 0.46 cSt (68 °F (20 °C))

Molecular formulaC6-H14Molecular weight86.17 g/molOxidizing propertiesNot oxidizing.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. May cause

drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

 Hexanes
 SDS US

 945636
 Version #: 01
 Revision date: Issue date: 22-January-2019
 5 / 9

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (nervous system) through prolonged or repeated exposure by

inhalation.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. May cause damage to organs through prolonged or

repeated exposure.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

3.9

Mobility in soil The product is insoluble in water and will spread on water surfaces.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1208

UN proper shipping name Hexanes (HEXANES RQ = 5,000 lbs)

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group II

Environmental hazards

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB2, T4, TP1

Packaging exceptions 150
Packaging non bulk 202
Packaging bulk 242

IATA

UN number UN1208 UN proper shipping name Hexanes

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards Yes.
ERG Code 3H

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1208 UN proper shipping name HEXANES

Transport hazard class(es)

Class 3

Subsidiary risk
Packing group ||

Environmental hazards

Marine pollutant Yes.

EmS F-E, S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

General information DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not established.

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Hexanes (CAS 110-54-3) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Toxic Substances Control

This substance is on the TSCA 8(b) inventory and is designated "active".

Act (TSCA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Yes

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

Hazard not otherwise classified (HNOC)

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. Hexanes 110-54-3 100

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Hexanes (CAS 110-54-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Hexanes (CAS 110-54-3)

US. New Jersey Worker and Community Right-to-Know Act

Hexanes (CAS 110-54-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Hexanes (CAS 110-54-3)

US. Rhode Island RTK

Hexanes (CAS 110-54-3)

California Proposition 65



WARNING: This product can expose you to Hexanes, which is known to the State of California to cause birth

defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Hexanes (CAS 110-54-3) Listed: December 15, 2017

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Hexanes (CAS 110-54-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Hexanes 8/9 945636 Version #: 01 Revision date: -Issue date: 22-January-2019

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 22-January-2019

Revision date - 01

HMIS® ratings Health: 3*

Flammability: 3 Physical hazard: 0

Disclaimer Greenfield Global USA, Inc. cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.