

Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)

# SAFETY DATA SHEET

## Isopropyl Alcohol 10%

### 1. IDENTIFICATION OF SUBSTANCE / MIXTURE AND OF SUPPLIER

**Product Identifier:** High Purity Chemicals  
**Synonyms:** Isopropanol; Isopropyl Alcohol; 2-Propanol; sec-propyl alcohol; dimethylcarbinol; sec-propanol; Rubbing alcohol; 1-Methylethanol; IPA 10%; propan-2-ol  
**Other means of identification:** CAS No. 67-63-0  
EINECS No. 200-661-7

**Recommended use of the chemical and restrictions on use:**

General Use Solvent

**Supplier Details:**

**Greenfield Global USA, Inc.**  
1101 Isaac Shelby Drive, Shelbyville,  
KY 40065, USA.  
Tel: 502.232.7600  
Fax: 502.633.6100  
CCN17213

**Greenfield Global USA, Inc.**  
58 Vale Road, Brookfield,  
CT 06804, USA.  
Tel: 203.740.3471  
Fax: 203.740.3481  
CCN17213

**Emergency Contact:** CHEMTREC: 1.800.424.9300 (USA) / +1.703.527.3887 (International)

### 2. HAZARDS IDENTIFICATION

**OSHA Hazards:**

Flammable liquid, Target Organ Effect, Irritant

**Target Organs:**

Cardiovascular system, Gastrointestinal tract, Kidney, Liver, Nerves

**NFPA**



on: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)

GHS label elements, including precautionary statements



**Signal Word:**  
DANGER!

**Hazard statement(s)**

H225	Highly flammable liquid and vapor.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

**Precautionary statement(s)**

P264	Wash hands thoroughly after handling.
P337 + P313	If eye irritation persists: Get medical attention.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves and eye and face protection.
P312	Call a POISON CENTER or doctor/ physician if you feel unwell.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P405	Store locked up.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, and lighting equipment.
P242	Use only non-sparking tools.
P102	Keep out of reach of children.
P210	Keep away from heat, sparks, open flames, and hot surfaces. No smoking.
P501	Dispose of contents and container to an approved waste disposal plant.
P233	Keep container tightly closed.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fumes/gas/mist/vapors.
P303 + P361 + P353	IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)**

P403 + P233

Store in a well-ventilated place. Keep container tightly closed. **1.800.527.9387 (INT)**

P403 + P235

Store in a well-ventilated place. Keep cool.

#### GHS Classification(s)

Eye irritation (Category 2A)

Flammable Liquids (Category 2)

Specific target organ toxicity - single exposure (Category 3)

**Other hazards which do not result in classification:**

#### Potential Health Effects:

Organ	Description
Eyes	Causes eye irritation.
Ingestion	May be harmful if swallowed.
Inhalation	May be harmful if inhaled. Causes respiratory tract irritation. Vapors may cause drowsiness and dizziness.
Skin	Harmful if absorbed through skin. Causes skin irritation.

### 3. COMPOSITION AND INFORMATION ON INGREDIENTS

**Chemical identity:**

Isopropyl Alcohol 10%

**Common name / Synonym:**

Isopropanol; Isopropyl Alcohol; 2-Propanol; sec-propyl alcohol; dimethylcarbinol; sec-propanol; Rubbing alcohol; 1-Methylethanol; IPA 10%

**CAS number:**

67-63-0

**EINECS number:**

200-661-7

**ICSC number:**

0554

**RTECS #:**

NT8050000

**UN #:**

UN1219

**EC #:**

603-117-00-0

% Weight	Material	CAS
10	Isopropyl Alcohol	67-63-0
90	Water	7732-18-5

### 4. FIRST AID MEASURES

#### General advice

Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### Skin

Immediately flush affected area with plenty of water while removing contaminated clothing. Wash contaminated

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)**  
clothing before reuse. Contact a doctor. If irritation persists, get medical attention. **+1.703.527.3887 (INT)**

#### **Inhalation**

Remove person to fresh air. If signs/symptoms continue, get medical attention. Give oxygen or artificial respiration as needed.

#### **Eyes**

Thoroughly flush the eyes with large amounts of clean low-pressure water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation persists, seek medical attention.

#### **Ingestion**

DO NOT induce vomiting. If vomiting does occur, have victim lean forward to prevent aspiration. Rinse mouth with water. Seek medical attention. Never give anything by mouth to an unconscious individual.

---

## **5. FIRE FIGHTING MEASURES**

#### **Suitable (and unsuitable) extinguishing media:**

SMALL FIRE: Use dry chemicals, CO<sub>2</sub>, water spray or alcohol-resistant foam. LARGE FIRE: Use water spray, water fog or alcohol-resistant foam. Cool all affected containers with flooding quantities of water.

#### **Special protective equipment and precautions for firefighters:**

Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Keep unopened containers cool by spraying with water.

#### **Unusual Fire and Explosion Hazards:**

- May produce a floating fire hazard.
- Static ignition hazard can result from handling and use.
- Vapors may settle in low or confined spaces.
- Vapors may travel to source of ignition and flash back.

Carbon oxides expected to be the primary hazardous combustion product.

#### **Flammable Properties**

##### **Classification**

OSHA/NFPA Class IB Flammable Liquid.

##### **Flash point**

18.3 °C (64.9 °F) - Closed Cup

##### **Autoignition temperature**

399 °C (750 °F)

---

## **6. ACCIDENTAL RELEASE MEASURES**

#### **Personal precautions, protective equipment and emergency procedures:**

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)**

Do not inhale vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. #P.703.527.9887 (INT)  
to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

**Environmental precautions:**

Stop leak. Contain spill if possible and safe to do so. Prevent product from entering drains.

**Methods and materials for containment and cleaning up:**

Contain spill, then collect with an electrically protected vacuum cleaner or by wet-brushing and put the material into a convenient waste disposal container. Keep container closed.

## 7. HANDLING AND STORAGE

**Precautions for safe handling:**

Do not get on skin or in eyes. Do not inhale vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. Open and handle container with care. Metal containers involved in the transfer of this material should be grounded and bonded.

**Conditions for safe storage, including any incompatibilities:**

Store under nitrogen. Keep container tightly closed in a dry and well- ventilated location. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Handle and store under an inert gas. Avoid moisture.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Control parameters, e.g., occupational exposure limit values or biological limit values:**

**Occupational Exposure Limits**

Component	Source	Type	Value	Note
Isopropyl Alcohol	US (ACGIH)	TWA	200 ppm	
Isopropyl Alcohol	US (ACGIH)	STEL	400 ppm	
Isopropyl Alcohol	US (OSHA)	TWA	400 ppm	
Isopropyl Alcohol	US (OSHA)	STEL	500 ppm	

**Appropriate engineering controls:**

General room or local exhaust ventilation is usually required to meet exposure limit(s). Electrical equipment should be grounded and conform to applicable electrical code.

**Individual protection measures, such as personal protective equipment:**

**Respiratory protection:**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)**  
tested and approved under appropriate government standards such as NIOSH (US) or CE (EU). **1.800.527.3887 (INT)**

**Hand protection:**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

**Eye protection:**

Use chemical safety goggles and/or a full face shield where splashing is possible. Use equipment approved by appropriate government standards, such as NIOSH (US) or EN166 (EU) Maintain eye wash fountain and quick-drench facilities in work area.

**Skin and body protection:**

Wear impervious, flame retardant, antistatic protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Hygiene measures:**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance ( <i>physical state, color, etc.</i> )	Liquid. Colorless, clear.
Freezing point	-89 °C (-127 °F)
Initial boiling point and boiling range	83 °C (181°F)
Flash point	18.3°C (64.9 °F) - Closed Cup
Flammability (solid, gas)	Flammable
Upper / Lower flammability or explosive limits	2% (V) / 12.7% (V)
Vapor pressure	43.2 hPa (32.4 mmHg) at 20.0 °C (68.0 °F)
Vapor Density	2.1
Solubility(ies)	soluble
Auto-ignition temperature	399 °C (750°F)
Formula (ISOPROPYL ALCOHOL)	C3H8O
Formula (WATER)	H2O
Molecular Weight (ISOPROPYL ALCOHOL)	60.1 g/mol
Molecular Weight (WATER)	18.02 g/mol

## 10. STABILITY AND REACTIVITY

Possibility of hazardous reactions	Vapors may form explosive mixture with air.
Conditions to avoid (e.g., static discharge, shock or vibration)	Heat, flames, and sparks. Extreme temperatures and direct sunlight.
Incompatible materials	Oxidizing agents, Acid anhydrides, Aluminium, Halogenated compounds, Acids

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)**

<b>Hazardous decomposition products</b>	Hazardous decomposition products formed upon heating or burning: Carbon oxides
---	---

## 11. TOXICOLOGICAL INFORMATION

- Water 7732-18-5

### Product Summary:

Do data available for the teratogenic, mutagenic, or reproductive toxicity effects of this product.

### Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

### Other Hazards

Organ	Description
Inhalation	May cause respiratory tract irritation upon inhalation.

- Isopropyl Alcohol 67-63-0

### Product Summary:

Long-term exposure (2 years) to Isopropyl Alcohol via inhalation at concentrations up to 5000 ppm caused no exposure related increases in tumors in animals. No data available for the teratogenicity, mutagenicity, or reproductive toxicity of this product. No data available to designate the product as causing specific target organ toxicity through repeated exposure. No data available to designate product as an aspiration hazard.

### Acute Toxicity:

LC50 (vapor)	Rat	19,000 ppm	8 hours
LD50 (oral)	Rat	4,396 mg/kg	
LD50 (skin)	Rabbit	12,870 mg/kg	

### Irritation:

#### Eyes

Rabbit - Irritating to eyes - 24 hours

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)**

**Eyes (ISOPROPANOL)**

Mildly irritating to the eye at an airborne concentration of 400 ppm, unpleasant at 800 ppm.

**Skin**

Moderate skin irritant

**Carcinogenicity**

IARC: Group 3: Not classifiable as to its carcinogenicity to humans.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**Other Hazards**

Organ	Description
Eyes	Produces irritation, characterized by a burning sensation, redness, tearing, inflammation, and possible corneal injury. May cause transient corneal injury
Ingestion	Causes gastrointestinal irritation with nausea, vomiting and diarrhea. May cause kidney damage. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure.
Inhalation	Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. May cause narcotic effects in high concentration. Causes upper respiratory tract irritation. Inhalation of vapors may cause drowsiness and dizziness. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal. The probable oral lethal dose in humans is 240 ml (2696 mg/kg), but ingestion of only 20 ml (224 mg/kg) has caused poisoning.
Skin	May cause irritation with pain and stinging, especially if the skin is abraded. Isopropanol has a low potential to cause allergic skin reactions; however, rare cases of allergic contact dermatitis have been reported. May be absorbed through intact skin. Dermal absorption has been considered toxicologically insignificant.
Chronic	Prolonged exposure can be irritating to mucous membranes, skin, and the respiratory system. Can cause liver and kidney damage.

---

## 12. ECOLOGICAL INFORMATION

- Water 7732-18-5
-

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)**  
**Ecotoxicity (aquatic and terrestrial, where available): +1.703.527.3887 (INT)**

**Ecotoxicity**  
Not Applicable

**Persistence and degradability:**  
No data available

**Bioaccumulative potential:**  
No data available

**Other adverse effects:**  
No data available

- Isopropyl Alcohol 67-63-0
- 

**Ecotoxicity (aquatic and terrestrial, where available):**

**Acute Fish Toxicity (ISOPROPANOL)**

LC50 / 96 hours Pimephales promelas: 9,640 mg/L

**Toxic to Daphnia and Other Aquatic Invertebrates**

EC50 / 24 h / Water Flea - 5,102 mg/L

**Toxicity to Aquatic Plants (ISOPROPANOL)**

EC50 / 72 hours Scenedesmus subspicatus > 1,000 mg/L

**Persistence and degradability:**  
No data available

**Bioaccumulative potential:**  
No data available

---

### 13. DISPOSAL CONSIDERATIONS

**Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

---

Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)

## 14. TRANSPORT INFORMATION

+1.703.527.3887 (INT)

Description of waste residues and information on their safe handling and methods of disposal:

UN number	UN1219
UN proper shipping name	Isopropanol
Transport hazard class(es)	3
Packing group (if applicable)	II

### IMDG

UN-Number: UN1219 Class: 3 Packing Group: II

EMS-No: F-E, S-D

Proper shipping name: ISOPROPANOL

Marine pollutant: No

### IATA

UN-Number: UN1219 Class: 3 Packing Group: II

Proper shipping name: Isopropanol

## 15. REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product in question:

### OSHA Hazards

Flammable liquid, Target Organ Effect, Irritant

All ingredients are on the following inventories or are exempted from listing

Country	Notification
Australia	AICS
Canada	DSL
China	IECS
European Union	EINECS
Japan	ENCS/ISHL
Korea	ECL
New Zealand	NZIoC
Philippines	PICCS
United States of America	TSCA

### SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

### SARA 313 Components

The following components are subject to reporting levels established by SARA title III, Section 313: ISOPROPYL ALCOHOL (CAS# 67-63-0) Revision date: 1987-01-01.

### SARA 311/312 Hazards

Acute Health Hazard

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)**  
Chronic Health Hazard  
Fire Hazard **+1.703.527.3887 (INT)**

**CERCLA**

No chemicals in this material with known CAS numbers are subject to the reporting requirements of CERCLA

**Massachusetts Right To Know Components**

Isopropyl Alcohol CAS-No. 67-63-0 Revision Date 1987-01-01

**Pennsylvania Right To Know Components**

Isopropyl Alcohol CAS-No. 67-63-0 Revision Date 1987-01-01

Water CAS-No. 7732-18-5

**New Jersey Right To Know Components**

Isopropyl Alcohol CAS-No. 67-63-0 Revision Date 1987-01-01

Water CAS-No. 7732-18-5

**California Prop 65 Components**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

---

## **16. OTHER INFORMATION: INCLUDING INFORMATION ON PREPARATION AND REVISION OF THE SDS**

**Disclaimer**

Greenfield Global USA, Inc. believes that the information on this SDS was obtained from reliable sources. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, Greenfield Global USA, Inc. does not assume responsibility and expressly disclaims liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS information may not be applicable. Information is correct to the best of our knowledge at the date of the SDS publication.